

K-WAX INTERNATIONAL CO., LTD No. 43, Sanlong St., Shulin Dist., New Taipei City 238, Taiwan(R.O.C.)

Tel. 886-2-86883099

## 1. Product And Company Identification

Product Name: K-WAX ® SuperCut A

Responsible Party: K-WAX INTERNATIONAL CO., LTD

No.43, Sanlong St., Shulin Dist., New Taipei City 238, Taiwan (R.O.C.)

**Emergency Information:** TEL. 886-2-86883099 FAX. 886-2-86883089

MSDS Date Of Preparation: 01/30/2018

Product Use and Uses Advised Against: Automotive maintenance product - For consumer and professional use

## 2. Hazards Identification

#### **EMERGENCY OVERVIEW**

May cause mild eye irritation. This product is not classified as hazardous as defined by 29 CFR 1910.1200 (OSHA Hazard Communication Standard) or Canada WHMIS.

# 3. Composition/Information On Ingredients

Component	CAS No.	Amount
Hydrotreatedheavynaphtha	64742-48-9	40-60%
Aluminium oxide	1344-28-1	5-10%
Carnauba wax	8015-86-9	10-15%
Silicone Fluid	9006-65-9	8-15%

## 4. First Aid Measures

Inhalation: If symptoms of exposure develop, remove to fresh air. Seek medical attention if symptoms persist.

**Skin Contact:** Rinse skin with plenty of water. If skin irritation or redness develops, seek medical attention.

Eye Contact: Flush eyes with plenty of water. If irritation or other symptoms persist, seek medical attention.

**Ingestion:** If the victim is fully conscious, have them drink a glass of water. Get medical assistance by calling a doctor or poison center. Never give anything by mouth to a person who is unconscious or drowsy.

### 5. Firefighting Measures

**Extinguishing Media:** Use dry chemical, carbon dioxide, foam, or water spray.

**Special Fire Fighting Procedures**: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored.

Unusual Fire Hazards: Closed containers may rupture if exposed to extreme heat.

**Hazardous Combustion Products:** Thermal decomposition will generate oxides of carbon and silicon and formaldehyde.

K-WAX ® SuperCut A



K-WAX INTERNATIONAL CO., LTD No. 43, Sanlong St., Shulin Dist., New Taipei City 238, Taiwan(R.O.C.) Tel. 886-2-86883099

## 6: Accidental Release Measures

Personal Precautions: Wear appropriate protective equipment.

**Environmental Precautions:** Prevent entry in storm sewers and waterways. Report spill as required by local and national regulations.

**Methods for Containment and Clean-Up:** Absorb with an inert material. Collect into a suitable container for disposal. Rinse area with water.

# 7. Handling and Storage

Avoid contact with eyes. Avoid prolonged contact with skin and clothing. Wash hands after use. Keep out of the reach of children.

No special storage required.

# 8. Exposure Controls / Personal Protection

CHEMICAL	EXPOSURE LIMIT
Non-Hazardous Ingredients	None Established

Ventilation: General ventilation should be adequate for all normal use.

Respiratory Protection: None required under normal use conditions.

Gloves: None normally required.

**Eye Protection:** None required for normal use. Avoid eye contact. Safety glasses or goggles are recommended if eye contact is possible.

Other Protective Equipment/Clothing: None required under normal use conditions.

# 9. Physical and Chemical Properties

Appearance And Odor: Opaque, Off-white viscous liquid with mild odor.

pH: ~8	Specific Gravity: ~1.0
Boiling Point: Not determined	Vapor Pressure: Not determined
Freezing Point: Not determined	Vapor Density: Not determined
Solubility In Water: Appreciable	Percent Volatile: Not determined
Coefficient Of Water/Oil Distribution: Notdetermined	Evaporation Rate: Not determined
Flash Point: Not applicable	Viscosity: ~ 2000 cP
	Autoignition Temp: Not determined
Flammability Limits: LEL: Not applicable	UEL: Not applicable

K-WAX ® SuperCut A Prepared by:Sam Zhang



K-WAX INTERNATIONAL CO., LTD No. 43, Sanlong St., Shulin Dist., New Taipei City 238, Taiwan(R.O.C.) Tel. 886-2-86883099

# 10. Stability and Reactivity

Stability: Stable

Conditions To Avoid: None. Incompatibility: Strongoxidizers.

Hazardous Decomposition Products: Thermal decomposition will generate oxides of carbon and silicon and

formaldehyde.

## 11. Toxicological Information

### **Acute Hazards:**

**Inhalation:** No adverse effects expected from the normal use of this product.

Skin Contact: Prolonged or repeated contact may cause mild irritation in some individuals.

Eye Contact: Direct contact may cause mild eye irritation with redness and tearing.

Ingestion: Swallowing may cause gastrointestinal disturbances.

Chronic Hazards: None currently known.

Medical Conditions Aggravated By Exposure: None currently known.

**Carcinogen:** None of the components at 0.1% or greater are listed as a carcinogen or potential carcinogen by IARC, NTP, ACGIH or OSHA.

## **Acute Toxicity Values:**

No toxicity data is currently available.

### 12. Ecological Information

No ecotoxicity data is currently available.

# 13. Disposal Considerations

Dispose of in accordance with all local, state/provincial and federal regulations. Offer empty containers for recycling.

### 14. Transport Information

General Transportation Statement This product does not require classification by DOT, IATA, ICAO or IMDG.

# 15. Regulatory Information

### **United States:**

**EPA TSCA INVENTORY**: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

**CERCLA Section 103:** This product has no RQ. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

K-WAX ® SuperCut A



K-WAX INTERNATIONAL CO., LTD No. 43, Sanlong St., Shulin Dist., New Taipei City 238, Taiwan(R.O.C.) Tel. 886-2-86883099

SARA Hazard Category (311/312): Not hazardous

**SARA 313:** This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None

## Canada:

Canadian WHMIS Classification: Not a controlled product.

Canadian Environmental Protection Act: All of the ingredients are listed on the Canadian DSL.

This MSDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the MSDS contains all of the information required by the CPR.

### 16. Other Information

NFPA Rating (NFPA 704): Health: 0 Fire: 0 Instability: 0 HMIS Rating: Health: 0 Fire: 0 Reactivity: 0

REVISION SUMMARY: May 3, 2021 Update to GHS SDS format and name change: Changes to all sections.

DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATIONAL SAFETY AND HEALTH

K-WAX ® SuperCut A Prepared by:Sam Zhang