



Material Safety Data Sheet

K-WAX INTERNATIONAL CO., LTD
No. 43, Sanlong St.,
Shulin Dist., New
Taipei City 238, Taiwan(R.O.C.)
Tel. 886-2-86883099

1. Product And Company Identification

Product Name: K-WAX ® Tar & Bug Remover

Responsible Party: K-WAX INTERNATIONAL CO., LTD
No.43, Sanlong St.,
Shulin Dist., New Taipei
City 238, Taiwan (R.O.C.)

Emergency Information: TEL. 886-2-86883099 FAX. 886-2-86883089

SDS Date of Preparation: 01/30/2018

Product Use and Uses Advised Against: Automotive maintenance product – For consumer and professional use

2. Hazards Identification

Note: This product is a consumer product and is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label will not contain the OSHA label elements shown below on this SDS.

GHS Classification:

Physical: Non-Hazardous	Health: Eye Irritant Category 2A Skin Sensitizer Category 1
-----------------------------------	--

GHS Label Elements:



WARNING!

Statements of Hazard	Precautionary Phrases
Causes serious eye irritation May cause an allergic skin reaction.	Wash exposed skin thoroughly after handling. Avoid breathing vapors, mist, or spray. Contaminated work clothing should not be allowed out of the workplace. Wear eye protection, and protective gloves. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. IF ON SKIN: Wash with plenty of water and soap. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.



Material Safety Data Sheet

K-WAX INTERNATIONAL CO., LTD
No. 43, Sanlong St.,
Shulin Dist., New
Taipei City 238, Taiwan(R.O.C.)
Tel. 886-2-86883099

Hazards not otherwise specified: None

Percentage of unknown toxicity: N/A

3. Composition/Information On Ingredients

Component	CAS No.	Amount
Petroleum Distillates	64742-14-9	70-80%
Surfactant	78330-21-9	5-8%
Toluene	108-88-3	10-15%

The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First Aid Measures

Inhalation: If symptoms of exposure develop, remove to fresh air. Seek medical attention if symptoms persist.

Skin Contact: Rinse skin with plenty of water. If skin irritation or rash develops, seek medical attention.

Eye Contact: Flush eyes with plenty of water for 15 minutes. If irritation or other symptoms persist, seek medical attention.

Ingestion: Do not induce vomiting unless directed to by a doctor or physician. If the victim is fully conscious, have them rinse their mouth with water. Get medical assistance by calling a doctor or poison center. Never give anything by mouth to a person who is unconscious or drowsy.

Most Important Symptoms: Eye contact causes irritation. May cause mild skin and respiratory irritation. May cause allergic skin reaction in some individuals.

Indication of Immediate Medical Attention/Special Treatment: Immediate medical attention should not be required.

5. Firefighting Measures

Suitable (and Unsuitable) Extinguishing Media: Use water fog, foam, carbon dioxide or dry chemical. Cool fire exposed containers with water.

Specific Hazards Arising from the Chemical: Closed containers may rupture if exposed to extreme heat. Thermal decomposition will generate Oxides of carbon and unknown materials.

Special Protective Equipment and Precautions for Fire-fighters: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored.

6: Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures: Wear appropriate protective equipment. Ventilate the area.



Material Safety Data Sheet

K-WAX INTERNATIONAL CO., LTD
No. 43, Sanlong St.,
Shulin Dist., New
Taipei City 238, Taiwan(R.O.C.)
Tel. 886-2-86883099

Environmental Precautions: Prevent entry in storm sewers and waterways. Report spill as required by local and national regulations.

Methods for Containment and Clean-Up: Absorb with an inert material. Collect into a suitable container for disposal. Rinse area with water.

7. Handling and Storage

Precautions for Safe Handling: Avoid contact with eyes. Avoid contact with skin and clothing. Avoid breathing vapors or mists. Wash exposed skin with soap and water after use. Keep out of the reach of children.

Conditions for Safe Storage, Including any Incompatibilities: No special storage required.

8. Exposure Controls / Personal Protection

Exposure Guidelines:

CHEMICAL	EXPOSURE LIMIT
Petroleum Distillates	100 ppm TWA OSHA PEL 400 mg/m ³ TWA OSHA PEL
Surfactant	None Established
Toluene	200 ppm TWA OSHA PEL 300 ppm Ceiling OSHA PEL

Engineering Controls: General ventilation should be adequate for all normal use. For operations where the recommended exposure limits are exceeded, forced ventilation such as local exhaust may be needed.

Personal Protective Equipment

Respiratory Protection: None required under normal use conditions. For applications where exposures may be excessive use a NIOSH approved organic vapor/dust mist respirator (mask) with appropriate eye protection. A full facepiece respirator provides both eye and respiratory protection. For higher concentrations an approved supplied air respirator (with escape bottle if required) or self-contained breathing apparatus may be required. Selection of respiratory protection depends on the contaminant type, form and concentration. Select in accordance with OSHA 1910.134 and good Industrial Hygiene practice.

Gloves: Rubber or other impervious gloves are recommended.

Eye Protection: Avoid eye contact. Safety glasses or goggles are recommended if eye contact is possible.

Other Protective Equipment/Clothing: None required under normal use conditions.



Material Safety Data Sheet

K-WAX INTERNATIONAL CO., LTD
No. 43, Sanlong St.,
Shulin Dist., New
Taipei City 238, Taiwan(R.O.C.)
Tel. 886-2-86883099

9. Physical and Chemical Properties

Appearance and Odor: liquid.

Physical State: liquid	Odor Threshold: Typical solvent
pH: Not determined	Specific Gravity: ~0.93
Initial Boiling Point/Range: Not determined	Vapor Pressure: Not determined
Melting/Freezing Point: Not determined	Vapor Density: Not determined
Solubility In Water: Not determined	Percent Volatile: >90%
Viscosity: Not determined	Evaporation Rate: Not determined
Coefficient Of Water/Oil Distribution: Not determined	VOC Content: Not determined
Flash Point: >93°C (>200°F)	Autoignition Temp: Not determined
Decomposition Temperature: Not determined	Flammability Limits: LEL: Not determined UEL: Not determined
Flammability (solid, gas): Not applicable	

10. Stability and Reactivity

Reactivity: Not normally reactive

Chemical Stability: Stable.

Possibility of Hazardous Reactions: None known

Conditions To Avoid: None known

Incompatible Materials: Strong oxidizing agents.

Hazardous Decomposition Products: Thermal decomposition will generate oxides of carbon and unknown materials.

11. Toxicological Information

POTENTIAL HEALTH EFFECTS:

Acute Hazards:

Inhalation: May cause mild irritation to mucous membranes and upper respiratory tract.

Skin Contact: May cause allergic skin reaction (sensitization) with itching or rash in susceptible individuals. May cause mild skin irritation.

Eye Contact: Causes eye irritation with redness, pain and tearing.

Ingestion: Swallowing may cause gastrointestinal disturbances.

Chronic Hazards: Prolonged exposure to dilute solutions may cause dermatitis.

Carcinogenicity Listing: None of the components is listed as a carcinogen or potential carcinogen by IARC, NTP, ACGIH or OSHA.



Material Safety Data Sheet

K-WAX INTERNATIONAL CO., LTD
No. 43, Sanlong St.,
Shulin Dist., New
Taipei City 238, Taiwan(R.O.C.)
Tel. 886-2-86883099

Acute Toxicity Values:

Petroleum Distillates:	LD50 Oral Rat >5,000 mg/kg LD50 Skin Rabbit >2,000 mg/kg
Surfactant:	LD50 Oral Rat >2,000 mg/kg LD50 Skin Rabbit >2,000 mg/kg
Toluene:	LD50 Oral Rat 636 mg/kg LD50 Skin Rabbit 14,100 mg/kg

12. Ecological Information

Ecotoxicity:

Petroleum Distillates:	LC50: Fish 45 mg/L/96 hr
Toluene:	LC50: Mouse 440 mg/L/24 hr
Surfactant:	LC50: Trout 240 mg/L/96 hr. EC50: Algae 180 mg/L/72 hr.

Persistence and Degradability: No data available

Bio accumulative Potential: No data available

Mobility in Soil: No data available

Other Adverse Effects: No data available

13. Disposal Considerations

Dispose of in accordance with all local, state/provincial and federal regulations. Offer empty containers for recycling.

14. Transport Information

General Transportation Statement This product does not require classification by DOT, IATA, ICAO or IMDG.

15. Regulatory Information

United States:

EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CERCLA Section 103: This product has no RQ. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA Hazard Category (311/312): Acute Health

SARA 313: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None



Material Safety Data Sheet

K-WAX INTERNATIONAL CO., LTD
No. 43, Sanlong St.,
Shulin Dist., New
Taipei City 238, Taiwan(R.O.C.)
Tel. 886-2-86883099

Canada:

Canadian Environmental Protection Act: All of the ingredients are listed on the Canadian DSL or the NDSL.

This SDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the SDS contains all of the information required by the CPR.

16. Other Information

NFPA Rating (NFPA 704):	Health: 2	Fire: 0	Instability: 0
HMIS Rating:	Health: 2	Fire: 0	Physical Hazard: 0

REVISION SUMMARY: May 3, 2021 Update to GHS SDS format and name change: Changes to all sections.

DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATIONAL SAFETY AND HEALTH